

# Drymec

## COMBO D LUX with digital programming

The DRYMEC Combo de Lux is an all in one timed drain with integral ball valve & strainer plus digital cycle time programming. It has a maximum discharge rate of 1000 l/hr and can operate in pressures up to 21 bar. The large 4 mm orifice protected by a ball valve and in line strainer makes it ideal for all types of compressed air installations.

Maximum compressor capacity	Unlimited
Inlet connection	¼" female or ½" male – same connector
Outlet connection	½" male
Minimum system pressure	0 bar
Maximum system pressure	21 bar
Minimum medium temperature	2° C
Maximum medium temperature	55° C
Valve orifice	4 mm
Type of operating valve	Direct acting
Valve seals	Viton (FPM)
Valve housing material	Brass
Test button	Yes
Timer housing material	ABS – fire resistant
Coil insulation	Grade H
Din connection	Form A
D Lux timer	Digital programming
On – off	mille seconds to 99 hours



DRYMEC Ltd.  
Unit 4R Bramhall Moor Technology Park  
Pepper Road  
Hazel Grove  
Stockport SK7 5BW

Tel 0161 487 4747  
Fax 0161 487 3778  
[www.drymec.com](http://www.drymec.com)  
[sales@drymec.com](mailto:sales@drymec.com)