

# Drymec

## MAGY magnetically operated zero loss condensate drain

The MAGY removes condensate from compressed air systems. The operation is automatic and there is no loss of valuable compressed air during condensate discharge.

The MAGY uses magnetic forces to operate the direct acting valve assembly and does not require an electrical supply. The magnets have been specially selected to ensure long and effective life.

### Key features :

Top or side inlet connection  
Supplied with vent adaptor union to prevent air locking  
Zero air loss during condensate discharge  
No electricity required to operate the drain  
Robust corrosion resistant aluminium casing

Drainage capacity	200 l/h
Inlets	2 x 1/2" top and side
Outlet	1/8"
Min operating pressure	0 bar
Max operating pressure	16 bar
Min operating temp	2° C
Max operating temp	50° C
Valve orifice	2 mm
Valve	Direct acting Stainless steel
Valve seals	Viton
Housing material	Corrosion resistant aluminium, EP coating
Dimensions	
Width	145 mm
Height	103 mm
Length	122 mm
Weight	kg 1.6



DRYMEC Ltd.  
Unit 4R Bramhall Moor Technology Park  
Pepper Road  
Hazel Grove  
Stockport SK7 5BW

Tel 0161 487 4747  
Fax 0161 487 3778  
[www.drymec.com](http://www.drymec.com)  
[sales@drymec.com](mailto:sales@drymec.com)