


Drymec

Duplex compressed air filters

Drymec duplex filters offer a space saving, economical filtration solution. Duplex filters combine a 0.01 micron coalescing element to reduce oil concentrations and an activated carbon element to remove odours and tastes. Maximum working pressure is 16 barg and maximum working temperature is 50° C.

Model	Pipe size	cfm	A	B	C	D	kg
D 028 XAC	1/4"	25	70	163	159	70	0.9
D 038 XAC	3/8"	35	70	163	159	70	0.9
D 058 XAC	1/2"	50	70	204	200	70	1.0
D 059 XAC	1/2"	70	100	240	236	80	2.3
D 078 XAC	3/4"	85	100	240	236	80	2.3
D 079 XAC	3/4"	125	100	360	356	80	3.1
D 108 XAC	1"	135	100	360	356	80	3.1
D 109 XAC	1"	175	100	360	356	80	3.2

Model	Element
D 028 XAC	E0406XA/E0407 DAC
D 038 XAC	E0407XA/E0407 DAC
D 058 XAC	E0413XA/E0413 DAC
D 059 XAC	E0613XA/E0613 DAC
D 078 XAC	E0613XA/E0613 DAC
D 079 XAC	E0620XA/E0625 DAC
D 108 XAC	E0620XA/E0625 DAC
D 109 XAC	E0625XA/E0625 DAC



DRYMEC Ltd.
 Unit 4R Bramhall Moor Technology Park
 Pepper Road
 Hazel Grove
 Stockport SK7 5BW

Tel 0161 487 4747
 Fax 0161 487 3778
www.drymec.com
sales@drymec.com