

Drymec

F T oil removing filters

This range of filters is designed to offer protection against air compressor oil carry over and inhaled atmospheric contaminants.

Standard	Internal float drain
Options	Differential indicator Differential gauge Differential gauge with alarm LED Manual drain ATD 16 external float drain TEC 11 timed solenoid drain



Technical data

Model	Flow rate		Conn ⁿ	Element	Dimensions		Weight kg
	Nm ³ /h	cfm			W	H mm	
FT* 008	51	30	3/8"	T* 008	85	187	0.77
FT* 012	72	42	1/2"	T* 012	85	187	0.77
FT* 108	111	65	3/4"	T* 018	85	256	0.88
FT* 030	198	116	1"	T* 030	125	263	2.20
FT* 055	330	194	1 1/2"	T* 055	125	362	2.60
FT* 080	486	286	1 1/2"	T* 080	125	452	2.90
FT* 120	750	441	1 1/2"	T* 120	125	643	3.70
FT* 160	1008	593	2"	T* 160	160	695	7.40
FT* 250	1560	918	2 1/2"	T* 250	160	935	10.00
FT* 400	2520	1483	3"	T* 400	250	1170	25.00

*Filtration grades P 3 micron S 1 micron X 0.01 micron Z activated carbon

DRYMEC Ltd.
Unit 4R Bramhall Moor Technology Park
Pepper Road
Hazel Grove
Stockport SK7 5BW

Tel 0161 487 4747
Fax 0161 487 3778
www.drymec.com
sales@drymec.com