

Drymec

NEA point of use dryers

NEA dryers are a simple safeguard for point of use applications. There are 4 cartridge options to cover requirements such as instrumentation, gas analysers or pneumatic control etc.

The housing is manufactured from aluminium with an anti corrosion treatment. The units are supplied with a manual drain valve.

A moisture indicator is supplied as an option to monitor the condition of the cartridge.

It is recommended that an oil removal filter is installed before the dryer and that the compressed air is at ambient temperature.

Maximum working pressure is 16 bar g

Capacity m³/h

Model	A4	AL	HC	CAS
NEA 115	-	-	15	18
NEA 220	-	-	25	33
NEA 226	7	8	50	48
NEA 232	-	-	120	65
NEA 340	18	21	155	80
NEA 351	31	36	320	-

Dimensions mm

Model	Port	W	D	H
NEA 115	½"	90	86	201
NEA 220	¾"	134	128	350
NEA 226	1"	134	128	507
NEA 232	1¼"	134	128	507
NEA 340	1½"	158	154	529
NEA 351	2"	158	154	787

DRYMEC Ltd.

Unit 4R Bramhall Moor Technology Park
Pepper Road
Hazel Grove
Stockport SK7 5BW



Tel 0161 487 4747
Fax 0161 487 3778
www.drymec.com
sales@drymec.com