

# Drymec

## SEPREMIUM 2 Oil water separator

The Sepremium range of oil/water separators separates oil from condensate generated by compressed air systems. The Sepremium achieves separation of oil from condensate by means of directing the condensate through various separation stages.

As condensate flows into the SEPREMIUM, the oil is filtered out through various filtration elements. The oil adsorbing elements are designed to combine various types of adsorption technologies to achieve less than 10 ppm oil residue values at the output stage.

The package includes a fixing bracket allowing for floor or wall mounting.

### Technical advantages

- High performance elements installed.
- Simple installation and maintenance procedures.
- Successful separation of mineral oil and synthetic lubricants.
- Special elements available for Ultra-Coolant\*, Sigma Mol and Roto-Inject\* applications.
- Fixing bracket included.



### Technical data

Maximum oil adsorption	2 litres
Inlet connection	1/2"
Outlet connection	1/2"
Housing material	ABS
Maximum compressor capacity	2 m <sup>3</sup> /min 65 cfm

### Separation of

Mineral lubricants	Yes
Synthetic lubricants	Yes
Stable condensate emulsion	Yes
Polyglycol – consult Drymec Ltd	Yes

Dimensions	255 x 230 x 239 high
------------	----------------------

\* Roto-inject, Ultra-Coolant and Sigma Mol are oil brands available in the market for air compressor lubrication

DRYMEC Ltd.  
Unit 4R Bramhall Moor Technology Park  
Pepper Road  
Hazel Grove  
Stockport SK7 5BW

Tel 0161 487 4747  
Fax 0161 487 3778  
[www.drymec.com](http://www.drymec.com)  
[sales@drymec.com](mailto:sales@drymec.com)